RECEIPT # 400-00-00-00-00-00-00-00-00-00-00-00-00-	ocument 1	Filed 10/27/2004	Page 1 of 16
OCAL RULE 4.1 IN THE UNITE		STRICT COURT S	
BY DPTY. CLE DIST	TRICT OF MA	ASSACHUSETTS 2394 00T 27	P 2: 4b
INNER-TITE CORP.	)	U.S. DISTAT THE TRICK !	
Plaintiff,	)		
v.	)	Civil Action 1	No.
DEWALCH TECHNOLOGIES, IN	C. )	04 - 40	219 FOS
Defendant.	)		

## **COMPLAINT**

Plaintiff, Inner-Tite Corp. ("Inner-Tite"), for its Complaint against defendant Dewalch Technologies, Inc. ("Dewalch"), alleges as follows:

- 1. This action for patent infringement arises under the patent laws of the United States, 35 U.S.C. § 100 et seq. This Court has jurisdiction pursuant to the provisions of 28 U.S.C. §1338(a). Venue is proper in this district pursuant to the provisions of 28 U.S.C. § 1391 and 28 U.S.C.§ 1400(b).
- 2. Inner-Tite is a corporation duly organized and existing under the laws of the Commonwealth of Massachusetts, with its principal place of business at 110 Industrial Drive, Holden, Massachusetts 01520.
- 3. Upon information and belief, Dewalch is a Texas corporation having its principal place of business at 6850 Wynnwood Lane, Houston, Texas 77008-5024.
- 4. Inner-Tite is the assignee of all right, title and interest in and to U.S.

  Patent No. 6,763,691, including all claims for damages by reason of past infringement of

said patent. U.S. Patent No. 6,763,691 (hereafter referred to as "the '691 patent") was duly and legally issued by the United States Patent and Trademark Office on July 20, 2004. A copy of the '691 patent is attached hereto as Exhibit A.

- 5. Upon information and belief, Dewalch sells utility security products, including the ringless meter socket lock shown in the photograph attached hereto as Exhibit B (hereafter referred to as "the accused product").
- 6. Upon information and belief, subsequent to the issuance of the 691' patent, Dewalch has committed acts of infringement and continues to infringe the '691 patent by manufacturing, offering for sale and selling the accused product.
  - 7. Upon information and belief, such infringement is willful.
- 8. Dewalch's infringement has caused and will continue to cause damages and irreparable injury to Inner-Tite, for which there is no adequate remedy at law.

WHEREFORE, Plaintiff Inner-Tite prays for judgment against the defendant Dewalch:

- A. Holding that the accused product infringes U.S. Patent No. 6,763,691.
- B. Ordering that Dewalch, its agents, servants, and employees and anyone acting in concert with it be enjoined and restrained permanently from infringing U.S. Patent No. 6,763,691 by manufacturing, offering for sale or selling the accused product.
- C. Awarding Inner-Tite judgment against Dewalch for its damages, and that those damages be trebled.

D. Awarding Inner-Tite judgment against Dewalch for interest, costs,
disbursements, attorney's fees and all such other and further relief that the
Court deems just and proper.

Respectfully Submitted,

Inner-Tite Corp.

By its attorneys

Date: October 27, 2004

Maurice E. Gauthier, BBO# 187340 William E. Hilton, BBO# 559515

Gauthier & Connors, LLP 225 Franklin Street, Suite 3300

Boston, Massachusetts 02110

(617) 426 - 9180

# (12) United States Patent Rafferty

(10) Patent No.:

US 6,763,691 BI

(45) Date of Patent:

Jul. 20, 2004

(54)	METER	BOX	LOCK	<b>ASSEMBLY</b>
1-	,			

(75)	Inventor:	Robert I	. Rafferty,	, Rutland, MA (US)	į
------	-----------	----------	-------------	--------------------	---

(73) Assignee: Inner-Tite Corporation, Holden, MA

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 268 days.

(21) Appl. No.: 09/795,701

Feb. 28, 2001 (22) Filed:

(51) Int. Cl.<sup>7</sup> ...... B65D 55/14 

(58) Field of Search ...... 109/1 R, 1 S, 109/23, 26, 31, 38, 48, 49.5, 50, 52, 54, 58.5, 59 R, 65; 269/53, 54.1, 76, 89, 41, 143, 249; 70/32–34, 63, 159–173, 77, 232, DIG. 34; 292/281, 288, 256, DIG. 11, 340,

341.18; 361/664-669

#### (56)References Cited

### U.S. PATENT DOCUMENTS

1,053,328 A		2/1913	Suters
1,241,459 A	*	9/1917	Woodard 188/45
1,262,795 A	*	4/1918	Holen 269/221
1,343,851 A		6/1920	Roe
1,554,958 A		9/1925	Faik
2,121,386 A	*	6/1938	Henrickson 114/203
3,088,560 A		5/1963	Preuss
3,181,319 A		5/1965	Hudon
3,275,363 A	*	9/1966	Bates et al 292/228
3,431,004 A		3/1969	Schell
3,867,822 A		2/1975	Morse et al.
3,938,839 A	*	2/1976	Collier 292/258
4,031,722 A		6/1977	Michelman et al.
4,080,811 A	٠	3/1978	Nielsen, Jr 70/164
4,096,718 A		6/1978	Michelman et al.

4,107,959 A	*	8/1978	Sharzynski et al	70/159
4,120,182 A	*	10/1978	Michelman et al	70/63
4,144,729 A	*	3/1979	Nielsen, Jr	70/63
4,152,910 A	*	5/1979	Swisher	70/159
4,202,574 A	*	5/1980	Redmayne	. 292/228
4,254,647 A	*	3/1981	Finck, Jr	70/77
4,326,395 A		4/1982	DeRosa	
4,414,829 A	*	11/1983	Nielsen, Jr. et al	70/160
4,475,365 A		10/1984	Swisher	
4,551,999 A		11/1985	Guiler	
4,986,096 A		1/1991	Soehner et al.	
5,007,258 A	+	4/1991	Mahaney	70/159
5,315,849 A	+	5/1994	Georgopoulos	
5,870,911 A		2/1999	DeWalch	

<sup>\*</sup> cited by examiner


Primary Examiner-Robert J. Sandy Assistant Examiner-Ruth C. Rodriguez

(74) Attorney, Agent, or Firm-Gauthier & Connors

#### (57)ABSTRACT

A lock assembly for use in combination with an electric meter box or other like enclosure having a bottom, a side wall, and a cover which may be opened to gain access to the interior of the box, and which when closed, overlaps an upper edge of the side wall. The lock assembly includes a bracket having first and second mutually spaced flanges integrally joined by an intermediate web. A jaw is mechanically interengaged with and carried by the bracket for movement between its flanges. The bracket is configured for removable mounting on the side wall, with its intermediate web interposed between the cover and the upper edge of the side wall, and with the first flange and the jaw respectively located adjacent exterior and interior surfaces of the side wall. The jaw is urged towards the first flange to clamp the side wall therebetween, and a cap is secured to the bracket. The cap has a lip configured and dimensioned to overlap and maintain the cover in a closed position.


## 8 Claims, 5 Drawing Sheets




U.S. Patent

Jul. 20, 2004


Sheet 1 of 5





**U.S. Patent** Jul. 20, 2004


Sheet 3 of 5 US 6,763,691 B1




U.S. Patent

Jul. 20, 2004

Sheet 4 of 5







U.S. Patent

Jul. 20, 2004

Sheet 5 of 5





## US 6,763,691 B1

### 1

## METER BOX LOCK ASSEMBLY

#### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

This invention relates generally to electric meter boxes and other like utility: equipment enclosures, and is concerned in particular with an improved lock assembly for preventing unauthorized access to the interiors of such 10 boxes.

#### 2. Description of the Prior Art

It is known to provide lock assemblies with exterior caps having lips that overlap and thus prevent unauthorized opening of meter box covers. Many of those lock 15 assemblies, such as for example those described in U.S. Pat. No. 4,107,959 (Skarzynski et al.); U.S. Pat. No. 4,120,182 (Michelman et al.); U.S. Pat. No. 4,144,729 (Nielsen); U.S. Pat. No. 4,475,365 (Swisher); and U.S. Pat. No. 5,315,849 (Georgopoulos) are fixed in place by means of bolts extend- 20 ing through holes in the side walls of the meter boxes. This complicates installation, requiring the use of hand tools to drill or punch out the required bolt holes, and requires workmen to reach into the box interiors to tighten the bolts during installation.

Other lock assemblies, such as those disclosed in U.S. Pat. Nos. 4,031,732 (Michelman et al.); U.S. Pat. No. 4,080,811 (Nielsen) and U.S. Pat. No. 4,096,718 (Michelman et al.) avoid piercing the meter box side walls, relying instead on mounting brackets that overlap the upper edges of the side 30 walls and that are secured in place by retaining screws bearing directly against the interiors of the side walls. Experience has shown, however, that the retaining screws are vulnerable to being bent or frictionally dislodged when external components of the lock assemblies are hammered, pried or otherwise forced by those seeking to gain unauthorized access to the box interiors. The Mounting brackets are thus loosened and ultimately disengaged from the box side walls, resulting in failure of the lock assemblies.

Attempts to force the lock assemblies can also overly stress and thus defeat the barrel locks used to interconnect lock assembly components.

The objective of the present invention is to avoid the above-noted problems by providing an improved lock 45 assembly that is easy to install without having to employ tools to drill, punch or otherwise breach the side wall of the meter box, and that once installed, is highly resistant to being dislodged or otherwise compromised by those seeking to gain unauthorized access to the box interior.

#### SUMMARY OF THE INVENTION

The lock assembly of the present invention is designed for use on an electric meter box or other like enclosure having a bottom wall, a side wall, and a cover that may be opened 55 to gain access to the box interior, and that when closed, overlaps an upper edge of the side wall. The lock assembly includes a -mounting bracket having first and second mutually spaced flanges integrally joined by an intermediate web. A jaw is mechanically interengaged with and carried by the 60 mounting bracket for movement between the first and second flanges. The bracket is configured and dimensioned for mounting on the side wall, with its intermediate web interposed between the cover and the upper edge of the side wall, and with its first flange and the movable jaw located respec- 65 tively adjacent exterior and interior surfaces of the side wall. A manually adjustable device, for example a screw, is

threaded through the second flange and serves to secure the bracket in place by urging the jaw towards the first flange to clamp the box side wall therebetween. A cap with a lip overlapping the cover coacts in interlocked engagement with the thus secured bracket.

These and other features and advantages of the present invention will now be described in greater detail with reference to the accompanying drawings, wherein:

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view, with portions broken away, of a conventional meter box employing a lock assembly in accordance with the present invention;

FIG. 2 is a sectional view on an enlarged scale taken along lines 2—2 of FIG. 1;

FIG. 3 is an exploded perspective view of the basic components making up the lock assembly shown in FIGS. 1

FIG. 4 is a sectional view similar to FIG. 2 showing an alternative embodiment of a lock assembly in accordance with the present invention;

FIGS. 5A and 5B illustrate a further embodiment of a locking mechanism for securing the mounting bracket to the side wall of the meter box; and

FIGS. 6A and 6B are views similar to FIGS. 5A and 5B showing still another embodiment of a locking mechanism for the mounting bracket.

#### DESCRIPTION OF PREFERRED **EMBODIMENTS**

Referring initially to FIGS. 1 and 2, a conventional electric meter box is shown at 10. The meter box includes a bottom wall 12, a side wall 14, and a cover 16. The side wall has a stepped configuration defining an angled ledge 18 spaced beneath the upper edge 20. The rear edge of the cover is overlapped by and captured beneath a lip 22 formed integrally with the side wall. The box encloses an electric meter (not shown) having a glass dome 24 protruding through an opening in the cover. As can best be seen in FIG. 2, the cover 16 is dimensioned to overlap the upper edge 20 of the side wall 14, with a peripheral lip 16a arranged to surround the top edge when the cover is in its closed position. A lock assembly 26 in accordance with one embodiment of the present invention serves to retain the cover in its closed position.

With further reference to FIG. 3, it will be seen that the lock assembly includes a mounting bracket 28 having first and second mutually spaced and angularly disposed flanges 30, 32 integrally joined by an intermediate web 34. A third flange 36 is formed integrally with and projects laterally from the first flange 30.

A jaw 38 has a stepped cross sectional configuration with angularly disposed flanges 40, 42 joined by a web 44. Teeth 46 project from one side of the web 44, and the flange 42 is cut away as at 48 to provide arms configured to interengage mechanically with notches in the sides of the flange 32 on mounting bracket 28.

A threaded boss 50 on flange 32 of the mounting bracket 28 accepts a manually adjustable thumb screw 52. The bracket 28 is configured for mounting on the side wall 14 of the meter box 10, with the intermediate web 34 extending over the upper edge 20 of the side wall, and with the first flange 30 of the bracket and the jaw 38 respectively located adjacent exterior and interior surfaces of the side wall. By manually tightening the thumb screw 52, the jaw is pivoted

3

in a clockwise direction (as viewed in FIG. 2), causing the teeth 46 to engage the interior surface of the side wall beneath the angled ledge 18. The side wall is thus securely clamped between the first bracket flange 30 and the jaw 38. The angled orientation of the second bracket flange 32 and the resulting upward projection of the thumb screw 52 makes it possible for bracket mounting to be accomplished without having to reach into the interior of the meter box.

After the mounting bracket 28 has been secured to the box side wall, the cover is closed. A cap 54 is then employed to maintain the cover in its closed position. The cap has an externally projecting integral lip 56 and an internal recess 58 extending horizontally across a vertical blind bore 60. The recess 58 is configured to receive the third flange 36 of the mounting bracket 28, with the blind bore 60 aligned with an 15 aperture 62 in the third flange.

A conventional barrel lock 64 is received in the bore 60 and aligned aperture 62, thus serving to mechanically interlock the cap 54 to the third flange 36, with the lip 56 of the cap overlapping the box cover 16. Optionally, the upper end of the barrel lock may be recessed within a protective ferrule 66 received in an enlarged diameter upper end of the blind bore 60.

In the alternative embodiment disclosed in FIG. 4, the mounting bracket: 28a again includes first and second flanges 30a, 32a joined by an intermediate web 34a. But here, the flanges 30a, 32a are arranged in parallel, resulting in the thumb screw 52 projecting horizontally into the box interior. Also, the jaw 38a is configured and arranged to be urged by the thumb screw 52 into horizontal sliding movement and into engagement with the interior surface of the box wall, again beneath the angled ledge 18.

The blind bore 60a of the cap 54a is separated from the recess 58a by an internal shelf 68 having an aperture 70 extending vertically therethrough. The aperture 70 is aligned with a threaded bore 62a in the third flange 36a of the bracket 28a, and a screw 72 extends through the shelf aperture 70 into threaded engagement with the threaded bore 62a in the third flange 36a to effect mechanical interengagement of the cap 54a with the mounting bracket 28a.

A sleeve 74 is secured, as for example by press fitting, into the vertical bore 60a. The sleeve cooperates with the barrel lock 64 to block access to the screw 72.

Force exerting means other than the thumb screws 52 <sup>45</sup> shown in FIGS. 2-4 may be employed to urge the jaws 38, 38a against the interior surfaces of the box walls. For example, as shown in FIGS. 5A and 5B, the second flange 32b of the bracket 28b may be equipped with a rotatable cam 76 operated by means of a handle 78. When unlocked, as shown in FIG. 5A, the cam allows freedom of movement of the jaw 38b relative to the bracket flanges 30a, 32b to thereby accommodate mounting of the bracket on the box side wall.

The bracket may then be locked in place by depressing the handle 78, as shown in FIG. 5B, to rotate the cam 76 against the jaw 38b, thus urging the jaw into its locked position.

In the embodiment shown in FIGS. 6A and 6B, the mounting bracket 28b also includes first and second flanges 30b, 32b joined by an intermediate web 34b. Flange 32b carries a cam 80 rotatable about an axis "A". A force exerting means in the form of a spring 82 resiliently urges the cam to rotate in a counterclockwise direction. In FIG. 6A, the cam has been rotated in a clockwise direction against the biasing action of the spring and into an open position to accommodate mounting of the bracket on the side wall 14 of

4

the meter box. In FIG. 6B, the cam has been released, and the biasing action of the spring has caused the cam to rotate in a counterclockwise direction, bringing the toothed periphery 84 of the cam into engagement with the interior surface of the box side wall 14 beneath the angled ledge 18.


In light of the foregoing, it will now be appreciated by those skilled in the art that the present invention offers a number of significant advantages as compared to prior art lock assemblies.


For example, the lock assembly may be installed without having to drill, punch or otherwise breach the side wall of the meter box. Installation can be readily accomplished without having to employ tools such as drills, punches and the like.

The interposition of a movable jaw between the interior box side wall and the force exerting means (thumb screw 52, cams 76, 80 or the like) insures that the force exerting means is safeguarded from being bent or frictionally dislodged by stresses resulting from attempts to defeat the lock assembly by hammering, prying or otherwise forcing the external cap. Such stresses are absorbed by the external cap and the mounting bracket, leaving the barrel lock largely unaffected. I claim:

- 1. For use in combination with a utility box having a bottom, a side wall, and a cover which may be opened to gain access to the interior of the box, and which when closed, overlaps an upper edge of the side wall, a lock assembly for maintaining the cover in its closed position, said lock assembly comprising:
- a bracket having first and second mutually spaced flanges integrally joined by an intermediate web;
- a jaw mechanically interengaged with and carried by said bracket for movement between said first and second flanges, said bracket being configured for removable mounting on said side wall, with said intermediate web interposed between said cover and the upper edge of said side wall, and with said first flange and said jaw respectively located adjacent exterior and interior surfaces of said side wall;
- force exerting means for urging said jaw towards said first flange to thereby clamp said side wall therebetween;
- a cap having a lip configured and dimensioned to overlap said cover; and interlocking means for securing said cap to said bracket.
- 2. The lock assembly of claim 1 wherein the side wall of said box is provided with an interior ledge spaced below said upper edge, and wherein said jaw engages said side wall beneath said ledge.
- 3. The lock assembly of claims 1 or 2 wherein said jaw includes at least one tooth engageable with said side wall.
- 4. The lock assembly of claim 1 wherein said force exerting means comprises a screw threaded through said second flange.
- 5. The lock assembly of claim 4 wherein said jaw includes a plurality of teeth engageable with said side wall.
- 6. The lock assembly of claim 1 wherein said jaw is pivotally connected to said second flange.
- 7. The lock assembly as claimed in claim 1 wherein said second flange is inclined at an acute angle with respect to said first flange.
- 8. The lock assembly as claimed in claim 1 wherein said bracket is provided with a third flange projecting from said first flange, and wherein said interlocking means said third flange.

\* \* \* \* \*







Case 4:04-cv-40219-FDS Document 1

AMOUN

RECEIPT #

APPLYING IFP

Filed 10/27/2004 Page 15 of 16  $\mathbf{\Omega} \mathbf{\Lambda} = \mathbf{\Lambda} \mathbf{0} \mathbf{2} \mathbf{1}^{-1} \mathbf{9}^{-1}$ 

SJS 44 (Rev. 3/99)

CIVIL COVER SHEAD

The JS-44 civil cover sheet and the information contained herein neither replace nor supplement the filing and service of pleadings or other papers as required by law, except as provided by local rules of court. This form, approved by the Judicial Conference of the United States in September 1974, is required for the use of the Clerk of Court for the purpose of initiating the civil docket sheet. (SEE INSTRUCTIONS OF THE FORM.) DEFENDANTS I. (a) PLAINTIFFS Dewalch Technologies, Inner Tite Corp. Inc. (b) County of Residence of First Listed Plaintiff Worcester, MA County of Residence of First Listed (INUS PLAINTIFF CASES ONLY) (EXCEPT IN U.S. PLAINTIFF CASES) NOTE: IN LAND CONDEMNATION CASES, USE THE LOCATION OF THE LAND INVOLVED. Attorneys (If Known) (c) Attorney's (Firm Name, Address, and Telephone Number) (617) 426-9180 unknown Maurice E. Gauthier Gauthier & Connors, LLP 225 Franklin Street, Suite 3300 Boston, MA II. BASIS OF JURISDICTION (Place an "X" in One Box Only) III. CITIZENSHIP OF PRINCIPAL PARTIES(Place an "X" in One Box for Plaintiff (For Diversity Cases Only) nd One Box for De fendant) DEF Citizen of This State □ 1  $\Box$  1 Incorporated or Principal Place 4 X 3 Federal Ouestion ☐ 1 U.S. Government. of Business In This State Plaintiff (U.S. Government Not a Party) Citizen of Another State 

2  $\square$  2 Incorporated and Principal Place 5 **K** 5 2 U.S. Government 4 Diversity Defendant (Indicate Citi zenship of Parties of Business In Another State in Item III) Citizen or Subject of a 

3 

3 Foreign Nation  $\Box$  6  $\Box$  6 Foreign Country (Place an "X" in One Box Only) IV. NATURE OF SUIT CONTRACT TORTS FORFEITURE/PENALTY BANKRUPTCY OTHER STATUTES ☐ 110 Insurance PERSONAL INJURY 422 Appeni 28 USC 158 400 State Resp portionment PERSONAL INJURY 610 Agriculture ☐ 362 Personal Injury— 620 Other Food & Drug 310 Airpiane 410 Antitrust 120 Marine ☐ 315 Airplane Product Med. Maipractice 625 Drug Related Scizure 423 Withdrawal 430 Banks and Banking 130 Miller Act 140 Negotiable Instrument Liability 🖺 365 Personal Injury of Property 21 USC 28 USC 157 450 Commerce/ICC Rates/etc. 320 Assault, Libel & Product Liability 630 Liquor Laws 460 Deportation 150 Recovery of Overpayment PROPERTY RIGHTS Slander & Enforcement o 368 Asbestos Personal 640 R.R. & Truck 470 Racke teer Influenced and 330 Federal Employers\* [ [998W88icare Act Injury Product 650 Airline Rogs. Corrupt Organizations 820 Copyrights ☐ 810 Selective Service ☐ 152 Recovery of Defaulted Liability Liability 660 Occupational K 830 Patent 850 Securities/Commodities/ PERSONAL PROPERTY Safety/Health Student Loans 340 Marine ☐ 840 Trademark (Excl. Veterans) 345 Marine Product 370 Other Fraud  $\Box$ 690 Other Exchange 371 Truth in Lending 875 Customer Challenge ☐ 153 Recovery of Overpayment Liability LABOR SOCIAL SECURITY of Veteran's Benefits 350 M otor V chicle 380 Other Personal 12 USC 3410 355 M otor V ehicle 160 Stockholders' Suits Property Damage 891 Agricultural Acts 710 Fair Labor Standards 861 H IA (13 95ff) 385 Property Damage 190 Other Contract Product Liability 892 Economic Stabilization Act 862 Black Lung (923) ☐ 360 Other Personal Injury ☐ 195 Contract P roduct Liability 893 Environm ental Matters Product Liability ☐ 720 Labor/M gmt. Relation: 863 DIW C/DIW W (405 (g)) ◻ 894 Energy Allocation Act REAL PROPERTY CIVIL RIGHTS PRISONER PETITIONS 864 SSID Title XVI 895 Freedom of ☐ 865 RS I (405(g)) 730 Labor/M gmt.Reporting Information Act ☐ 510 M otions to Va cate 210 Land Condemnation 441 Voting & Disclosure Act 900 Appeal of Fee Determination qual Access to FEDERAL TAX SUITS 740 Railway Labor Act 220 Foreclosure 442 Employment Sentence 230 Ront Losse & Electment 443 Housing/ Habeas Corpus: ☐ 870 Taxes (U.S. Plaintiff Justice 240 Torts to Land Accommod ations ☐ 530 General 790 Other Labor Litigation or Defendant) 950 Constitutionality of 245 Tort Product Liability 444 W cifare  $\Box$ 535 De ath Penalty State Statutes 440 Other Civil Rights 290 All Other Real Property 540 Mandamus & Other 791 Empl. Ret. Inc. B71 IRS -Third Party 890 Other Statutory Actions 550 Civil Rights Security Act 26 USC 7609 ☐ 555 Prison Condition (PLACE AN "X" IN ONE BOX ONLY) Appeal to V. ORIGIN Transferred from District Judge from another district X1 1 Reinstated or 🗆 5  $\square$  3  $\Box$  4 (specify) 6 Multidistrict Original Removed from Remanded from Magistrate State Court Reopened Proceeding Appellate Court Litigation Judgment VI. CAUSE OF ACTION (Cite the U.S. Civil Statute underwhich you are filing and write beef statement of cause. Patent Infringement under 35 USC§100 et seq. DEMAND S CHECK YES only if demanded in complaint: VII. REQUESTED IN ☐ CHECK IF THIS IS A CLASS ACTION UNDER F.R.CP. 23 ☐ Yes X No COMPLAINT: JURY DEMAND: VIII. RELATED CASE(S) instructions): JUDG IF ANY DOCKET NUMBER E SIGNATURE OF ATTORNEY OF RECORD DATE FOR OFFICE USE ONLY

JUDGE

MAG. JUDGE

# Case 4:04-cv-40219-FDS Document 1

Filed 10/27/2004 109216 bf 6

## UNITED STATES DISTRICT COURT DISTRICT OF MASSACHUSETTS

Title of cas	se (name o	of first party on each		Inner Tite (				<del> </del>
				Dewalch Tech				
Category i	n which tl	ne case belongs base	ed upon the nu	mbered nature of su	it code liste	d on the civil o	over sheet. (S	See
local rule	40.1(a)(1)).							
		160, 410, 470, R.23, R	EGARDLESS (	OF NATURE OF SUIT				
X	il.	195, 368, 400, 440, 4 740, 790, 791, 820*, 8	41-444, 540, 5 330*, 840*, 850	50, 555, 625, 710, 72 ), 890, 892-894, 895,	:0, 730, 950.	•	te AO 120 or A ademark or cop	
		110, 120, 130, 140, 1 315, 320, 330, 340, 3 380, 385, 450, 891.	51, 190, 210, 2 45, 350, 355, 3	230, 240, 245, 290, 3 360, 362, 365, 370, 3	10, 71,			
		220, 422, 423, 430, 4 690, 810, 861-865, 87			50, 660,			
	٧.	150, 152, 153.						
Title and i this distri	number, if ct please i	any, of related cases indicate the title and r	s. (See local runumber of the	ule 40.1(g)). If more t first filed case in this	than one prices court.	or related case	has been filed	in
nc	ne							
Has a pric	or action t	petween the same par	rties and base	d on the same claim	ever been fi	led in this cou	rt?	
Does the 28 USC §		in this case question	the constituti	onality of an act of c	ongress affe	octing the publi	c interest? (S	ie e
If so, is th	e U.S.A. d	or an officer, agent or	employee of t	he U.S. a party?	em		***************************************	
				N.A.	YES _	NO		
is this ca	se require	d to be heard and de	termined by a	district court of three	e judges pur YES	suant to title 2	8 USC §2284?	
Do <u>all</u> of t Massacht 40.1(d)).	the parties usetts ("g	in this action, excluors overnmental agencie	uding governm es"), residing i	ental agencies of the in Massachusetts re	united stateside in the s	es and the Cor ame division?	nmonwealth of - (See Local R	tule
					IES (	K NO		
	A.	If yes, in which divis	sion do <u>all</u> of t	he non-governmenta	<del>y</del>			
		Eastern Division		Central Division	X	Western	Division	
	В.	If no, in which divisi agencies, residing			or the only p	parties, exclud	ing governmen	tal
		Eastern Division		Central Division		Western	Division	
		Removal - are there a			urt requiring	the attention	of this Court?	(If
				N.A.	YES	NO		
ASE TYPE O		Maurice E.	Gauthier	-				
RNEY'S NA					root S:	ita 3300	Boston	MA 02110
		C& Connors,	111 ZZ	Franklin St	reer au	Tre 3300	DOS COILS	121 02110
PHONE NO.	617	-426-9180		<del></del>				